

Tel: 508-987-0121  
 Fax: 508-987-1233  
 email: sales@flairamerica.com

# FILTERABLE COOLING PUMP



Unit : m/m

SPECIFICATION	HP (KW)	H	L	A	B	C	D	E	F	PCD	W
MODEL NO.											
SP - 8100	1/8 (0.09)	250	100	7.2	69	106	97	124	156	115~129	7.2
SP - 8130	1/8 (0.09)	280	130	7.2	69	106	97	124	156	115~129	7.2
SP - 8150	1/8 (0.09)	300	150	7.2	69	106	97	124	156	115~129	7.2
SP - 8180	1/8 (0.09)	330	180	7.2	69	106	97	124	156	115~129	7.2
SP - 8200	1/8 (0.09)	350	200	7.2	69	106	97	124	156	115~129	7.2
SP - 8220	1/8 (0.09)	370	220	7.2	69	106	97	124	156	115~129	7.2
SP - 6100	1/6 (0.13)	250	100	7.2	69	106	97	124	156	115~129	7.2
SP - 6130	1/6 (0.13)	280	130	7.2	69	106	97	124	156	115~129	7.2
SP - 6150	1/6 (0.13)	300	150	7.2	69	106	97	124	156	115~129	7.2
SP - 6180	1/6 (0.13)	330	180	7.2	69	106	97	124	156	115~129	7.2
SP - 6200	1/6 (0.13)	350	200	7.2	69	106	97	124	156	115~129	7.2
SP - 6220	1/6 (0.13)	370	220	7.2	69	106	97	124	156	115~129	7.2
SP - 6270	1/6 (0.13)	420	270	7.2	69	106	97	124	156	115~129	7.2
SP - 4155	1/4 (0.18)	335	155	8	69	133	120	160	189	148~163	9
SP - 4180	1/4 (0.18)	365	180	8	69	133	120	160	189	148~163	9
SP - 4200	1/4 (0.18)	385	200	8	69	133	120	160	189	148~163	9
SP - 4220	1/4 (0.18)	405	220	8	69	133	120	160	189	148~163	9
SP - 4240	1/4 (0.18)	425	240	8	69	133	120	160	189	148~163	9
SP - 4270	1/4 (0.18)	455	270	8	69	133	120	160	189	148~163	9
SP - 4350	1/4 (0.18)	535	350	8	69	133	120	160	189	148~163	9
SP - 3155	1/3 (0.25)	335	155	8	98	133	120	160	189	148~163	9
SP - 3180	1/3 (0.25)	365	180	8	98	133	120	160	189	148~163	9
SP - 3200	1/3 (0.25)	385	200	8	98	133	120	160	189	148~163	9
SP - 3220	1/3 (0.25)	405	220	8	98	133	120	160	189	148~163	9
SP - 3240	1/3 (0.25)	425	240	8	98	133	120	160	189	148~163	9
SP - 3270	1/3 (0.25)	455	270	8	98	133	120	160	189	148~163	9
SP - 3350	1/3 (0.25)	535	350	8	98	133	120	160	189	148~163	9
SP - 2150	1/2 (0.37)	370	150	8.5	69	145	136	168	199	150~180	10
SP - 2180	1/2 (0.37)	400	180	8.5	69	145	136	168	199	150~180	10
SP - 2290	1/2 (0.37)	460	290	8.5	69	145	136	168	199	150~180	10
SP - 2340	1/2 (0.37)	510	340	8.5	69	145	136	168	199	150~180	10
SP - A150	3/4 (0.56)	370	150	8.5	98	145	136	168	199	150~180	10
SP - A180	3/4 (0.56)	400	180	8.5	98	145	136	168	199	150~180	10
SP - A290	3/4 (0.56)	460	290	8.5	98	145	136	168	199	150~180	10
SP - A340	3/4 (0.56)	510	340	8.5	98	145	136	168	199	150~180	10
SP - 1180	1 (0.75)	420	180	10	69	162	154	190	215	169~210	10.2
SP - 1240	1 (0.75)	480	240	10	69	162	154	190	215	169~210	10.2
SP - 1290	1 (0.75)	530	290	10	69	162	154	190	215	169~210	10.2
SP - 1380	1 (0.75)	620	380	10	69	162	154	190	215	169~210	10.2
SP - Y180	1.5 (1.12)	420	180	10	98	162	154	190	215	169~210	10.2
SP - Y240	1.5 (1.12)	480	240	10	98	162	154	190	215	169~210	10.2
SP - Y290	1.5 (1.12)	530	290	10	98	162	154	190	215	169~210	10.2
SP - Y380	1.5 (1.12)	620	380	10	98	162	154	190	215	169~210	10.2

